

Model: AC4 ENDLESS 1L BROADWAY Codes: 100199463 - L167012873

Group: G-210

Format: 24,4X126,1X0,8

Thickness: 8 mm



COMPOSITION						
		Size Materia		Type of material		
	Layer 1	0.2	Melamine	Aminoplastic thermosetting resins		
	Layer 2	0.2	Decorative paper			
	Layer 3	8	HDF	High-density Fiber Board and water-repellent glues		
	Layer 4		Contracara	Hojas de papel kraft impregnadas con resinas fenólicas		

CERTIFICATIONS					
Carb certification	CARB: Phase II compliant				

FEATURES



Imitates the surface of wood



Beveled cut on the long sides of the board in order to create a





5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN



Format where only one board has been used to finish the entire base



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



23. Intensive residential



Abrasion-resistance level as per Standard UNE-EN 13329



Boards that have continuity between them, thus achieving the optical effect of much longer formats



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and $\,$ tear for their recommended End Use Category in accordance with EN 13329.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



32. General commercial







DIMENSIONAL FEATURES					
Item thickness	≤0.50 mm	EN 13329*			
Length of face	≤0.50 mm	EN 13329*			
Width of face	≤0.20 mm	EN 13329*			
Squareness of the item (q)	≤0.20 mm	EN 13329*			
Straightness of face	≤0.30 mm/m	EN 13329*			
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*			
Joint between items	≤0.20 mm	EN 13329*			
Difference in height among items	≤0.15 mm	EN 13329*			
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*			
Uv light fastness	≥4	EN 438-2,16*			

LABORATORY TESTS					
AC4	UNE EN 13329:2000*				
IC2	EN 13329*				
Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*				
4	EN 438*				
No damage	EN 424*				
No damage	EN 425*				
≤18%	UNE-EN 13329:2000*				
0.03%	EN 434:1994*				
E1	EN 717*				
Clase 2	EN 12633*				
Efl-s1	EN 13501*				
1.2 kV	ISO 1815*				
R=0.057 m2 K/W	ISO 8302*				
0.06 mm					
≤18%	ASTM D 1037*				
Class DS:≥0.30	EN 13893*				
Cfl	EN ISO 9239-1*				
s1	EN 13501-1*				
925 ±5 KG/M3	UNE EN 323*				
	AC4 IC2 Grado 5 (G 1 y 2) y Grado 4 (G 3) 4 No damage No damage ≤18% 0.03% E1 Clase 2 Efl-s1 1.2 kV R=0.057 m2 K/W 0.06 mm ≤18% Class DS:≥0.30 Cfl				

PACKING				
Boxes	2.4615 M2/CS			
Pallets	73.8442 M2/PAL			
Units	0.3077 M2/ST			
Sale unit	M2			
Base unit	ST			
Net weight	7.5727 KG/M2			
Gross weight	7.8652 KG/M2			

SPECIAL PIECES										
SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100153848	L167012512	IGUALACION ENDLESS 1L BROADWAY 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100176686	L167012696	MAMPERLAN AC4 ENDLESS 1L BROADWAY120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100153885	L167012515	TRANSICION ENDLESS 1L BROADWAY 4X270X1	G-155	20 ST/CS	1000 ST/PAL	92 ST/M2	ST	ST		
100153892	L167012482	ZOCALO ENDLESS 1L BROADWAY 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST





15/5/2019