

Model: AC4 ENDLESS 1L BROOKLYN**Codes:** 100199491 - L167012872**Group:** G-210**Format:** 24,4X126,1X0,8**Thickness:** 8 mm

COMPOSITION



	Size	Material	Type of material
Layer 1	0.2	Melamine	Aminoplastic thermosetting resins
Layer 2	0.2	Decorative paper	
Layer 3	8	HDF	High-density Fiber Board and water-repellent glues
Layer 4		Contracara	Hojas de papel kraft impregnadas con resinas fenólicas

CERTIFICATIONS

Carb certification	CARB: Phase II compliant
--------------------	--------------------------

FEATURES



Imitates the surface of wood



Beveled cut on the long sides of the board in order to create a continuity effect



20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Format where only one board has been used to finish the entire base surface



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



23. Intensive residential



Abrasion-resistance level as per Standard UNE-EN 13329



Boards that have continuity between them, thus achieving the optical effect of much longer formats



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



32. General commercial

DIMENSIONAL FEATURES

Item thickness	≤0.50 mm	EN 13329*
Length of face	≤0.50 mm	EN 13329*
Width of face	≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/m	EN 13329*
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*
Joint between items	≤0.20 mm	EN 13329*
Difference in height among items	≤0.15 mm	EN 13329*
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*
Uv light fastness	≥4	EN 438-2,16*

LABORATORY TESTS

Resistance to abrasion	AC4	UNE EN 13329:2000*
Impact resistance	IC2	EN 13329*
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*
Resistance to cigarette burns	4	EN 438*
Furniture leg effect	No damage	EN 424*
Castor chair effect	No damage	EN 425*
Swelling in thickness	≤18%	UNE-EN 13329:2000*
Dimensional stability	0.03%	EN 434:1994*
Formaldehyde emissions	E1	EN 717*
Slip resistance (cls)	Clase 2	EN 12633*
Fire resistance	Efl-s1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	1.2 kV	ISO 1815*
Heat resistance	R=0.057 m2 K/W	ISO 8302*
Curvature	0.06 mm	
Swelling in thickness	≤18%	ASTM D 1037*
Slip resistance (dcof)	Class DS:≥0.30	EN 13893*
Critical radiant flux	Cfl	EN ISO 9239-1*
Smoke density (burning)	s1	EN 13501-1*
Density of the board	925 ±5 KG/M3	UNE EN 323*

PACKING

Boxes	2.4615 M2/CS	
Pallets	73.8442 M2/PAL	
Units	0.3077 M2/ST	
Sale unit	M2	
Base unit	ST	
Net weight	7.6377 KG/M2	
Gross weight	7.9627 KG/M2	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100153849	L167012511	IGUALACION ENDLESS 1L BROOKLYN 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100176679	L167012697	MAMPERLAN AC4 ENDLESS 1L BROOKLYN120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100153886	L167012514	TRANSICION ENDLESS 1L BROOKLYN 4X270X1	G-155	20 ST/CS	1000 ST/PAL	92 ST/M2	ST	ST		
100153893	L167012479	ZOCALO ENDLESS 1L BROOKLYN 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST

