Model: AC4 ENDLESS 1L QUEENS Codes: 100199486 - L167012874 Group: G-210 Format: 24,4X126,1X0,8 Thickness: 8 mm

L'OC PORCELANOSA Grupo



		(COMPOSITI	ON			
		Size	Material	Type of material			
	Layer 1	0.2	Melamine	Aminoplastic thermosetting resins			
	Layer 2	0.2	Decorative pa	per			
	Layer 3	8	HDF	High-density Fiber Board and water-repellent glues			
	Layer 4		Contracara	Hojas de papel kraft impregnadas con resinas fenólicas			
		C	ERTIFICATIO	ONS			
Carb certification		CARB: Phase II c	ompliant				
			FEATURE	S			
Imitates the surface of wood			Ś	Boards that have continuity between them, thus achieving the optical effect of much longer formats			
Beveled cut on the long sides of the board in order to create a continuity effect			\mathbf{i}	Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together			
 5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329. 			ar and vith EN 20	13329.			
Format where only one board has been used to finish the entire base surface			re base	Is suitable for installing on water radiant heating			
PanEuropean Forest Cert origin of the products fro	PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests			Safety and joint durability are the main features of this easy installatio system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly			
23. Intensive residential	🕅 23. Intensive residential			🚯 32. General commercial			
AC4 Abrasion-resistance level	l as per Standard	UNE-EN 13329					



L'AC PORCELANOSA Grupo

	DIMENSIONAL FEATURES	
Item thickness	≤0.50 mm	EN 13329*
Length of face	≤0.50 mm	EN 13329*
Width of face	≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/m	EN 13329*
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*
Joint between items	≤0.20 mm	EN 13329*
Difference in height among items	≤0.15 mm	EN 13329*
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*
Uv light fastness	≥4	EN 438-2,16*

LABORATORY TESTS						
Resistance to abrasion	AC4	UNE EN 13329:2000*				
Impact resistance	IC2	EN 13329*				
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*				
Resistance to cigarette burns	4	EN 438*				
Furniture leg effect	No damage	EN 424*				
Castor chair effect	No damage	EN 425*				
Swelling in thickness	≤18%	UNE-EN 13329:2000*				
Dimensional stability	0.03%	EN 434:1994*				
Formaldehyde emissions	E1	EN 717*				
Slip resistance (cls)	Clase 2	EN 12633*				
Fire resistance	Efl-s1	EN 13501*				
Evaluation of propensity to accumulation of electrostatic charges	1.2 kV	ISO 1815*				
Heat resistance	R=0.057 m2 K/W	ISO 8302*				
Curvature	0.06 mm					
Swelling in thickness	≤18%	ASTM D 1037*				
Slip resistance (dcof)	Class DS:≥0.30	EN 13893*				
Critical radiant flux	Cfl	EN ISO 9239-1*				
Smoke density (burning)	s1	EN 13501-1*				
Density of the board	925 ±5 KG/M3	UNE EN 323*				

	PACKING	
Boxes	2.4615 M2/CS	
Pallets	73.8442 M2/PAL	
Units	0.3077 M2/ST	
Sale unit	M2	
Base unit	ST	
Net weight	7.7515 KG/M2	
Gross weight	8.0505 KG/M2	

SPECIAL PIECES										
SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100153849	L167012511	IGUALACION ENDLESS 1L BROOKLYN 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST		
100176687	L167012694	MAMPERLAN AC4 ENDLESS 1L QUEENS 120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100153886	L167012514	TRANSICION ENDLESS 1L BROOKLYN 4X270X1	G-155	20 ST/CS	1000 ST/PAL	92 ST/M2	ST	ST		
100153893	L167012479	ZOCALO ENDLESS 1L BROOKLYN 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST

