

Model: AC4 GENUINE 1L GREAT BASIN

Codes: 100173150 - L165003585


Group: G-210

Format: 19X125,7X0,8

Thickness: 8 mm



COMPOSITION



	Size	Material	Type of material
Layer 1	0.2	Melamine	Aminoplastic thermosetting resins
Layer 2	0.2	Decorative paper	
Layer 3	8	HDF	High-density Fiber Board and water-repellent glues
Layer 4		Contracara	Hojas de papel kraft impregnadas con resinas fenólicas

CERTIFICATIONS

Carb certification	CARB: Phase II compliant
--------------------	--------------------------

FEATURES



Texture similar to hand-smoothed wood



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Is suitable for installing on water radiant heating



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



32. General commercial



Beveled cut on all 4 edges of the board for emphasizing size



20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Format where only one board has been used to finish the entire base surface



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



23. Intensive residential



AC4 Abrasion-resistance level as per Standard UNE-EN 13329

DIMENSIONAL FEATURES

Item thickness	≤0.50 mm	EN 13329*
Length of face	≤0.50 mm	EN 13329*
Width of face	≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/m	EN 13329*
Flatness of item (f)	fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20%	EN 13329*
Joint between items	≤0.20 mm	EN 13329*
Difference in height among items	≤0.15 mm	EN 13329*
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*
Uv light fastness	7	EN 438-2,16*

LABORATORY TESTS

Resistance to abrasion	AC4	UNE EN 13329:2000*
Impact resistance	IC2	UNE EN 13329*
Resistance to cigarette burns	4	EN 438*
Furniture leg effect	No damage	EN 424*
Castor chair effect	No damage	EN 425*
Swelling in thickness	≤18%	UNE-EN 13329:2000*
Formaldehyde emissions	E1	EN 717*
Slip resistance (cls)	Class DS	EN 13893-2002*
Fire resistance	Efl-s1	EN 13501*
Heat resistance	R=0.054 m2 K/W	ISO 8302-1991*
Thermal conductivity	0.017 W/mK	UNE-EN 12667:2002*
Swelling in thickness	≤18%	ASTM D 1037*
Slip resistance (dcof)	Class DS:≥0.30	EN 13893*
Critical radiant flux	Cfl	EN ISO 9239-1*
Smoke density (burning)	s1	EN 13501-1*
Density of the board	1285 ±5 KG/M3	UNE EN 323*

PACKING

Boxes	2.1495 M2/CS	
Pallets	103.1746 M2/PAL	
Units	0.2388 M2/ST	
Sale unit	M2	
Base unit	ST	
Net weight	7.5995 KG/M2	
Gross weight	7.8131 KG/M2	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100174623	L167012666	IGUALACION LAMINADO ALUMINIO 4,5X270X1	G-155	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100174612	L167012667	TRANSICION LAMINADO ALUMINIO 4X270X1	G-155	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100155425	L167012495	ZOCALO LAMINADO BLANCO 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST