Model: ARTISAN 1L COCONUT Codes: 100103574 - L160803284

Group: G-268

Format: 19X190X1,5 Thickness: 15 mm



## ADDITIONAL NOTES

While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.060-0.070	Oil	Natur treatment			
	Layer 2	4	Hardwood Layer	Quercus spp			
	Layer 3	9	Intermediate Layer	Wood or HDF slats			
	Layer 4	2	Contracara	Madera de coníferas			

LABORATORY TESTS							
Mass per surface	>500 Kg/m2	EN 14342*					
Thermal conductivity	0.13 W/M*°K	UNE-EN 12667:2002*					
Heat resistance	0.11 M2*°K/W	UNE-EN 12667:2002*					
Formaldehyde emissions	E1	EN 717*					
Moisture content	8.00%	UNE-EN 13183-1/AC:2004*					
Flammability	Dfl-s1	EN 13501*					
Bulk density	740 Kg/m3	UNE-EN 323:1994*					
Slip resistance	45/63	UNE-CEN/TS 15676:2008*					
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*					
Critical radiant flux	Clase 1	ASTM E 648*					
Smoke density (burning)	<450 Dmc	ASTM E 662*					





14/5/2019



## **FEATURES**



This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the



The finish imitates traditional hand brushing of the wood, providing a rough and artisan look as the one cabinetmakers would achieve in the



Beveled cut on all 4 edges of the board for emphasizing size



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Format where only one board has been used to finish the entire base surface



It is necessary to apply adhesive for installing it.



Made with oak wood.



Material from a North American country



Structure consisting of an upper layer that has the noble look of the material, an intermediate layer of coniferous wood that compensates the tensions between the different parts, and a bottom plywood that provides dimensional stability.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Combination of oils and natural waxes with air drying that leave the wood with open pores. This type of oil penetrates into the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed. Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.



Is suitable for installing on water radiant heating



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



There are considerable color changes between pieces.



Material from a European country.



Noble layer

	PACKING	
Boxes	2.166 M2/CS	
Pallets	75.81 M2/PAL	
Sale unit	M2	
Base unit	ST	
Net weight	10.651 KG/M2	
Gross weight	11.2909 KG/M2	

SPECIAL PIECES										
SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100114965	L165002599	IGUALACION ARTISAN COCONUT 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100176565	L165003615	MAMPERLAN ARTISAN 1L COCONUT 120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100114967	L165002600	TRANSICION ARTISAN COCONUT 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100111711	L165002380	ZOCALO ARTISAN COCONUT 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST





14/5/2019