

**Model:** ARTISAN 1L WOVEN

**Codes:** 100103576 - L160803285

**Group:** G-268

**Format:** 19X190X1,5


**Thickness:** 15 mm



### ADDITIONAL NOTES

While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

### COMPOSITION



	Size	Material	Type of material
<b>Layer 1</b>	0.060-0.070	Oil	Natur treatment
<b>Layer 2</b>	4	Hardwood Layer	Quercus spp
<b>Layer 3</b>	9	Intermediate Layer	Wood or HDF slats
<b>Layer 4</b>	2	Contracara	Madera de coníferas

### LABORATORY TESTS

Mass per surface	>500 Kg/m <sup>2</sup>	EN 14342*
Thermal conductivity	0.13 W/M*K	UNE-EN 12667:2002*
Heat resistance	0.11 M <sup>2</sup> *K/W	UNE-EN 12667:2002*
Formaldehyde emissions	E1	EN 717*
Moisture content	8.00%	UNE-EN 13183-1/AC:2004*
Flammability	Dfl-s1	EN 13501*
Bulk density	740 Kg/m <sup>3</sup>	UNE-EN 323:1994*
Slip resistance	45/63	UNE-CEN/TS 15676:2008*
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*
Critical radiant flux	Clase 1	ASTM E 648*
Smoke density (burning)	<450 Dmc	ASTM E 662*

## FEATURES



This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation.



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Beveled cut on all 4 edges of the board for emphasizing size



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Format where only one board has been used to finish the entire base surface



It is necessary to apply adhesive for installing it.



Made with oak wood.



Material from a North American country.



Structure consisting of an upper layer that has the noble look of the material, an intermediate layer of coniferous wood that compensates the tensions between the different parts, and a bottom plywood that provides dimensional stability.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



The finish imitates traditional hand brushing of the wood, providing a rough and artisan look as the one cabinetmakers would achieve in the past.



Combination of oils and natural waxes with air drying that leave the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed. Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.



Is suitable for installing on water radiant heating



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



There are considerable color changes between pieces.



Material from a European country.



Noble layer

## PACKING

Boxes	2.166 M2/CS
Pallets	75.81 M2/PAL
Sale unit	M2
Base unit	ST
Net weight	10.3269 KG/M2
Gross weight	10.964 KG/M2

## SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100113809	L165002563	IGUALACION ARTISAN WOVEN 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100176558	L165003613	MAMPERLAN ARTISAN 1L WOVEN 120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100113831	L165002567	TRANSICION ARTISAN WOVEN 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100113839	L165002570	ZOCALO ARTISAN WOVEN 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST

