

Model: ESTOCOLMO NATURAL 22X90(A) Codes: 100145244 - V50500201 Water absorption: BIa - Porcelain tiles (E<=0.1%) Thickness: 10.5



| | DIMENSIONAL FEATURES | |
|-----------------------------------|--|----------------|
| UNE-EN ISO 10545-2 | | |
| Thickness | 10.5 | |
| Width | 220 | |
| Length | 900 | |
| Length and width deviation | Below 0.15% | <=0.5 %* |
| Side straightness deviation | Below 0.15% | <=0.5 %* |
| Squareness deviation | Below 0.15% | <=0.6 %* |
| Surface flatness deviation | Below 0.15% | <=0.5 %* |
| *ISO-13006:2012 UNE-EN 14411:2012 | | |
| | MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 | |
| Crazing resistance | Resists 3 cycles | |
| *ISO-13006:2012 UNE-EN 14411:2012 | | |
| | HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 | |
| Chemical resistance | Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" | CLASE B Min. * |
| Stain resistance | Class 5. Easy cleaning with water | CLASE 3 Min. * |
| *ISO-13006:2012 UNE-EN 14411:2012 | | |
| | SCOPE OF USE | |
| Technical code-1 | Use on heavy traffic floors | |
| | ANTI-SLIP VALUE UNE-ENV 12633:2003, DIN-51130 y ASTM C1028 | |
| Slip resistance (ramp) | R-9 | |
| *ISO-13006:2012 UNE-EN 14411:2012 | | |
| | PACKING | |
| Boxes | 1.188 M2/CS | |
| Pallets | 61.7761 M2/PAL | |
| Units | 0.198 M2/ST | |
| | | |

