Model: HERITAGE NATURAL 80X80(A)

Codes: 100190916 - P17601141

Water absorption: {VAL}BIa

Thickness: 11.2 mm

MATE / MATT

DESTONIFICADO
TONE VARIATIONS

DIMENSIONAL FEATURES
UNE-EN ISO 10545-2

Thickness	11.2 MM	
Width	800 MM	
Length	800 MM	
Length and width deviation	Below 0.15%	<=0.5 %*
Side straightness deviation	Below 0.15%	<=0.5 %*
Squareness deviation	Below 0.15%	<=0.6 %*
Surface flatness deviation	Below 0.15%	<=0.5 %*

*ISO-13006:2012 UNE-EN 14411:2012

MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

Breaking strength	3411 N	>1300 N*
Crazing resistance	Resists 3 cycles	

*ISO-13006:2012 UNE-EN 14411:2012

HYGIENIC FEATURES
UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases"	CLASE B Min. *
Stain resistance	Class 5. Easy cleaning with water	CLASE 3 Min. *

*ISO-13006:2012 UNE-EN 14411:2012

SCOPE OF USE

Technical code-1	Use on medium traffic floors	

ANTI-SLIP VALUE
UNE-ENV 12633:2003, DIN-51130 y ASTM C1028

Slip resistance (ramp)	R-10	

*ISO-13006:2012 UNE-EN 14411:2012

PACKING

Boxes	1.28 M2/CS	
Pallets	51.2 M2/PAL	
Units	0.64 M2/ST	

Certificaciones del sistema

Do not use cleaning agents containing hydrofluoric acid.
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.
For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique.
Mosaic tiles must be grouted.
This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.