

Model: LEGEND 1L LIGHT

Codes: 100110285 - L160803371

Group: G-257

Format: 26X220X1,5

Thickness: 15 mm



ADDITIONAL NOTES

While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Oil	Natur treatment
Layer 2	4	Hardwood Layer	Quercus spp
Layer 3	9	Intermediate Layer	Wood or HDF slats
Layer 4	2	Contracara	Madera de coníferas

LABORATORY TESTS

Mass per surface	>500 Kg/m ²	EN 14342*
Thermal conductivity	0.13 W/M*K	UNE-EN 12667:2002*
Heat resistance	0.11 M ² *K/W	UNE-EN 12667:2002*
Formaldehyde emissions	E1	EN 717*
Moisture content	8.00%	UNE-EN 13183-1/AC:2004*
Flammability	Dfl-s1	EN 13501*
Bulk density	740 Kg/m ³	UNE-EN 323:1994*
Slip resistance	35/58	UNE-CEN/TS 15676:2008*
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*

FEATURES



This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation.



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Format where only one board has been used to finish the entire base surface



It is necessary to apply adhesive for installing it.



Made with oak wood.



Material from a North American country.



Structure consisting of an upper layer that has the noble look of the material, an intermediate layer of coniferous wood that compensates the tensions between the different parts, and a bottom plywood that provides dimensional stability.



The finish imitates traditional hand brushing of the wood, providing a rough and artisan look as the one cabinetmakers would achieve in the past.



Combination of oils and natural waxes with air drying that leave the wood with open pores. This type of oil penetrates into the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed. Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.



Is suitable for installing on water radiant heating



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



There are consistent color changes between pieces.



Material from a European country.



Noble layer

PACKING

Boxes	3.432 M2/CS
Pallets	96.096 M2/PAL
Sale unit	M2
Base unit	ST
Net weight	8.1993 KG/M2
Gross weight	8.486 KG/M2

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net weight	Gross weight
100114235	L165002523	IGUALACION LEGEND LIGHT 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100176574	L165003637	MAMPERLAN LEGEND 1L LIGHT 120X7X3	G-163	2 ST/CS	200 ST/PAL	11 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100114251	L165002554	TRANSICION LEGEND LIGHT 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9 ST/M2	ST	ST	1 KG/ST	1 KG/ST
100114262	L165002541	ZOCALO LEGEND LIGHT 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5 ST/M2	ST	ST	1 KG/ST	1 KG/ST