Model: ONA BEIGE 33,3X59,2(A) Codes: 100115797 - V13499431 Water absorption: BIII Thickness: 9.5 mm





DIMENSIONAL FEATURES UNE-EN ISO 10545-2		
Thickness	9.5 MM	
Width	333 MM	
Length	590.5 MM	
Length and width deviation	Below 0.15%	<=0.5 %*
Side straightness deviation	Below 0.15%	<=0.5 %*
Squareness deviation	Below 0.15%	<=0.6 %*
Surface flatness deviation	Below 0.15%	<=0.5 %*
*ISO-13006:2012 UNE-EN 14411:2012		
MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
Crazing resistance	Resists 3 cycles	
*ISO-13006:2012 UNE-EN 14411:2012		
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
Chemical resistance	Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases"	CLASE B Min. *
Chemical resistance Stain resistance	Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" Class 5. Easy cleaning with water	CLASE B Min. * CLASE 3 Min. *
	bases"	
Stain resistance	bases"	
Stain resistance	bases" Class 5. Easy cleaning with water	
Stain resistance *ISO-13006:2012 UNE-EN 14411:2012	bases" Class 5. Easy cleaning with water SCOPE OF USE	
Stain resistance *ISO-13006:2012 UNE-EN 14411:2012	bases" Class 5. Easy cleaning with water SCOPE OF USE Use on walls	
Stain resistance *ISO-13006:2012 UNE-EN 14411:2012 Technical code-1	bases" Class 5. Easy cleaning with water SCOPE OF USE Use on walls PACKING	

Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.