


Model: PARK GRAY 33,3X100(A) Codes: 100156060 - V14401541 Water absorption: {VAL}BIII

Thickness: 12 mm







| DIMENSIONAL FEATURES UNE-EN ISO 10545-2 | | | | |
|---|-------------|----------|--|--|
| Thickness | 12 MM | | | |
| Width | 332.8 MM | | | |
| Length | 1000 MM | | | |
| Length and width deviation | Below 0.15% | <=0.5 %* | | |
| Side straightness deviation | Below 0.15% | <=0.5 %* | | |
| Squareness deviation | Below 0.15% | <=0.6 %* | | |
| Surface flatness deviation | Below 0.15% | <=0.5 %* | | |

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11

Resists 3 cycles Crazing resistance

*ISO-13006:2012 UNE-EN 14411:2012

*ISO-13006:2012 UNE-EN 14411:2012

| HYGIENIC FE | ATURES |
|--------------------|------------|
| LINE EN ISO 10545 | 12-14-1005 |

Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and Chemical resistance Class 5. Easy cleaning with water CLASE 3 Min. * Stain resistance

*ISO-13006:2012 UNE-EN 14411:2012

SCOPE OF USE

Technical code-1 Use on walls

| | ANTI-SLIP VALUE UNE-ENV 12633:2003, DIN-51130 y ASTM C1028 |
|----------------|---|
| Friction (dry) | 0 |

Friction (wet) 0

*ISO-13006:2012 UNE-EN 14411:2012

| PACKING | |
|---------------|--|
| 0.999 M2/CS | |
| 54.945 M2/PAL | |
| 0.333 M2/ST | |

System Certification





Boxes

Pallets Units