
PORCELANOSA Grupo

Model: RODANO LINEAL CALIZA 31,6X59,2(A) Codes: 100177523 - P23107151 Water absorption: BIII Thickness: 9.6 mm





Thickness 9.6 MM Width 314.98 MM Length 591 MM Length and width deviation Below 0.15% Squareness deviation Below 0.15% Surface flatness deviation Below 0.15% Straface flatness deviation Below 0.15% *ISO-13006:2012 UNE-EN 14411:2012 WECHANICAL FEATURES UNE-EN ISO 10545-4:6-7-11 Breaking strength 1235 N Crazing resistance Resists 3 cycles *ISO-13006:2012 UNE-EN 14411:2012 VECHANICAL FEATURES UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A" for swinming pools and cleaning products (Pasis's attack). Minimum Class "B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE Technical code-1 Use on walls PACKING Boxes 1.128 M2/CS	DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length591 MMControlLength and width deviationBelow 0.15%<=0.5 %*	Thickness	9.6 MM		
Length and width deviationBelow 0.15%<=0.5 %*Side straightness deviationBelow 0.15%<=0.6 %*	Width	314.98 MM		
Side straightness deviation Below 0.15% <=0.5 %*	Length	591 MM		
Squareness deviation Below 0.15% <=0.6 %*	Length and width deviation	Below 0.15%	<=0.5 %*	
Surface flatness deviation Below 0.15% <=0.5 %*	Side straightness deviation	Below 0.15%	<=0.5 %*	
ISO-13006:2012 UNE-EN 14411:2012 MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 >600 N Grazing resistance 1235 N >600 N* Crazing resistance Resists 3 cycles * *ISO-13006:2012 UNE-EN 14411:2012 HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A"" for swimming pools and cleaning products (resists attack), Minimum Class ""B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE Technical code-1 Use on walls PACKING Boxes 1.128 M2/CS	Squareness deviation	Below 0.15%	<=0.6 %*	
MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 Breaking strength 1235 N >600 N* Crazing resistance Resists 3 cycles > *ISO-13006:2012 UNE-EN 14411:2012 HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE Technical code-1 Use on walls PACKING Boxes 1.128 M2/CS	Surface flatness deviation	Below 0.15%	<=0.5 %*	
UNE-EN ISO 10545-4-6-7-11 Breaking strength 1235 N >600 N* Crazing resistance Resists 3 cycles * *ISO-13006:2012 UNE-EN 14411:2012 HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE E PACKING Itechnical code-1 Use on walls E Boxes 1.128 M2/CS	*ISO-13006:2012 UNE-EN 14411:2012			
Crazing resistance Resists 3 cycles *ISO-13006:2012 UNE-EN 14411:2012 HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 ECOPE OF USE Technical code-1 Use on walls Fachting Lass 0. Walls Dases 1.128 M2/CS		MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11		
ISO-13006:2012 UNE-EN 14411:2012	Breaking strength	1235 N	>600 N	
HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 Stain resistance CLASE 1 Min. * Technical code-1 Use on walls Image: Class 1 Min. * PACKING Boxes 1.128 M2/CS Image: Class 1 Min. *	Crazing resistance	Resists 3 cycles		
UNE-EN ISO 10545-13-14:1995 Chemical resistance Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases" CLASE B Min. * Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE Technical code-1 Use on walls Image: Clease 1.128 M2/CS Image: Clease 1.128 M2/CS	*ISO-13006:2012 UNE-EN 14411:2012			
Iresists attack). Minimum Class ""B"" for acids and bases" Stain resistance Class 5. Easy cleaning with water CLASE 3 Min. * *ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE Employed and the second and the sec	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995			
*ISO-13006:2012 UNE-EN 14411:2012 SCOPE OF USE Technical code-1 Use on walls PACKING Boxes 1.128 M2/CS	Chemical resistance	Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases"	CLASE B Min. *	
SCOPE OF USE Technical code-1 Use on walls PACKING Boxes 1.128 M2/CS	Stain resistance	Class 5. Easy cleaning with water	CLASE 3 Min. *	
Technical code-1 Use on walls PACKING Boxes 1.128 M2/CS	*ISO-13006:2012 UNE-EN 14411:2012			
PACKING Boxes 1.128 M2/CS	SCOPE OF USE			
Boxes 1.128 M2/CS	Technical code-1	Use on walls		
	PACKING			
	Boxes	1.128 M2/CS		
Pallets 81.2167 M2/PAL	Pallets	81.2167 M2/PAL		
Units 0.188 M2/ST	Units	0.188 M2/ST		



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.