PORCELANOSA GIUDO

Model: SEVILLA WHITE 20X31,6(A) Codes: 100214654 - P31498641 Water absorption: BIII Thickness: 9.2 mm





ness	9.2 MM	
1000		
h	198.3 MM	
:h	314.98 MM	
h and width deviation	Below 0.15%	<=0.5 %*
straightness deviation	Below 0.15%	<=0.5 %*
reness deviation	Below 0.15%	<=0.6 %*
ce flatness deviation	Below 0.15%	<=0.5 %*
13006:2012 UNE-EN 14411:2012		
	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11	
king strength	1278 N	>600 N*
ng resistance	Resists 3 cycles	
13006:2012 UNE-EN 14411:2012		
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
nical resistance	Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases"	CLASE B Min. *
resistance	Class 5. Easy cleaning with water	CLASE 3 Min. *
13006:2012 UNE-EN 14411:2012		
	SCOPE OF USE	
nical code-1	Use on walls	
PACKING		
5	1.1376 M2/CS	
ts	63.7047 M2/PAL	
	0.0632 M2/ST	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.