## PORCELANOSA Grupo

Model: TWIN BOTTEGA ACERO 45X120(A) Codes: 100214786 - P35800471 Water absorption: BIII Thickness: 10.3 mm





DIMENSIONAL FEATURES UNE-EN ISO 10545-2		
Thickness	10.3 MM	
Length and width deviation	Below 0.15%	<=0.5 %*
Side straightness deviation	Below 0.15%	<=0.5 %*
Squareness deviation	Below 0.15%	<=0.6 %*
Surface flatness deviation	Below 0.15%	<=0.5 %*
*ISO-13006:2012 UNE-EN 14411:2012		
	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11	
Breaking strength	1318 N/MM2	>600 N*
Crazing resistance	Resists 3 cycles	
*ISO-13006:2012 UNE-EN 14411:2012		
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
Chemical resistance	Class "A"" for swimming pools and cleaning products (resists attack). Minimum Class ""B"" for acids and bases"	CLASE B Min. *
Stain resistance	Class 5. Easy cleaning with water	CLASE 3 Min. *
*ISO-13006:2012 UNE-EN 14411:2012		
PACKING		
Boxes	1.62 M2/CS	
Pallets	64.7983 M2/PAL	
Units	0.54 M2/ST	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.