

Model: PRADA CALIZA 31,6X59,2(A) Codes: 100242661 - P32193261 Water absorption: BIII - Revestimiento (10%<=E<=20%) Thickness: 9 mm





 $\bigcirc$ 



	DIMENSIONAL FEATURES UNE-EN ISO 10545-2	
Thickness	9 mm	
Width	316 MM	
Length	592 MM	
Length and width deviation	Below 0.15%	<=0.5%*
Side straightness deviation	Below 0.15%	<=0.5%*
Squareness deviation	Below 0.15%	<=0.6%*
Surface flatness deviation	Below 0.15%	<=0.5%*
*ISO-13006:2018 UNE-EN 14411:2016		
	MECHANICAL FEATURES	
	UNE-EN ISO 10545-4-6-7-11	
Breaking strength	1236 N	>600N*
Modulus of rupture	24 N/MM2	>=12N/mm2*
Crazing resistance	Resists 3 cycles	
*ISO-13006:2018 UNE-EN 14411:2016		
	HYGIENIC FEATURES	
	UNE-EN ISO 10545-13-14:1995	
Chemical resistance	Class "A" for swimming pools and cleaning products	CLASE B Min.*
	(resists attack). Minimum Class "B" for acids and bases	
Stain resistance	Class 5. Easy cleaning with water	CLASE 3 Min.*
*ISO-13006:2018 UNE-EN 14411:2016		
	SCOPE OF USE	
Technical code-1	Use on walls	
	PACKING	
Boxes	1.128 M2/BOX	
Pallets	81.2167 M2/PAL	
Units	0.188 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.