

Model: PRADA WHITE 31,6X59,2(A)

Codes: 100242628 - P32193231

Water absorption: BIII - Revestimiento (10%≤E≤20%)

Thickness: 9 mm



DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Thickness	9 mm	
Width	316 MM	
Length	592 MM	
Length and width deviation	Below 0.15%	≤0.5%*
Side straightness deviation	Below 0.15%	≤0.5%*
Squareness deviation	Below 0.15%	≤0.6%*
Surface flatness deviation	Below 0.15%	≤0.5%*

*ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

Breaking strength	1166 N	>600N*
Modulus of rupture	23 N/MM2	>=12N/mm2*
Crazing resistance	Resists 3 cycles	

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	CLASE B Min.*
Stain resistance	Class 5. Easy cleaning with water	CLASE 3 Min.*

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

Technical code-1	Use on walls	
------------------	--------------	--

PACKING

Boxes	1.128 M2/BOX	
Pallets	81.2167 M2/PAL	
Units	0.188 M2/PIECE	

System Certification



Do not use cleaning agents containing hydrofluoric acid.
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.
For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.
Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.